

TOOLS & ACCESSORIES

URYU AIR TOOLS HORIZONTAL GRINDING TOOL FOR HD WORK.



OTR Buffer and skiving tool
7,200 RPM for OTR Tires
Powerful tool for heavy jobs.
Spec: 1,2hp / 7200rpm
Wheel capacity diameter 5"
Minimum air hose 1/2 inlet 3/8
average air consumption 11cfm
operating air pressure 90psi

CODE	DESCRIPTION	WEIGHT
48-125	UG-1250L OTR SKIVING TOOL	4kg



Heavy Duty High Speed Skiving tool
Powerful tool for fast buffing/skiving, rear exhaust,
lever throttle to control various speed.
Spec: ,60HP / 14 600rpm
wheel capacity diameter 2-1/2
minimum air hose 3/8 air inlet 1/4"
Average air consumption 7cfm
Operating air pressure 90psi

CODE	DESCRIPTION	WEIGHT
48-065	UG-65EBL HIGH SPEED SKIVING	2kg

LOW SPEED AIR TIRE BUFFERS

URYU HD LOW SPEED TIRE BUFFER.



Spec:
0,5hp / 5000rpm
Min air hose 3/8 inlet 1/4"
Average air consumption 14cfm
Operating air pressure 90psi

5000 RPM HEAVY DUTY LOW SPEED
BUFFER WITH QUICK CHANGE CHUCK

CODE	DESCRIPTION	WEIGHT
48-050	UD50S-45TBHD	850g

HD LOW SPEED TIRE BUFFER.



Spec:
0,5hp / 3000rpm
Min air hose 3/8 inlet 1/4"
Average air consumption 14cfm
Operating air pressure 90psi

Designed for conveniences,
the many features of the 327LS
make it the ideal tool for every tire
shop. Quick change chuck, built in
regulator and lever-style throttle.

CODE	DESCRIPTION	WEIGHT
48-327LS	IR327LS LOW SPEED	510g

LOW SPEED TIRE BUFFER.



Spec:
0,5hp / 2500rpm
Min air hose 3/8 inlet 1/4"
Average air consumption 4cfm
Operating air pressure 90psi

Economical, low speed buffer
with 3/8 quick change chuck and
rear exhaust hose.

CODE	DESCRIPTION	WEIGHT
48-873	CP873 LOW SPEED	510g

FEATURES:

- * Lever-style tease trigger with lock-off for easy operation and protection against accidental start-up
- * Quick change chuck for easy buffing wheel change
- * Pipe-away exhaust directs air away from work area and operator
- * Convenient hanger-keeps tool within easy reach